



<b>CPU</b>	ARM9, 400 MHz	X	AVR 8bit, 32 MHz	
<b>Memory</b>	128 MB RAM, 1GB Flash	X	16 KB RAM / 6 MB Flash	
<b>Proof of Data</b>	Non volatile memory	X	X	X
<b>Date / Time</b>	Realtime cclock	X	X	X
<b>Interface</b>	USB Mass storage / USB HID	X	USB Mass storage	USB serial
	USB Ethernet / USB Serial	X	USB serial	
<b>Programming</b>	Eclipse IDE for C/C++	X	-	-
<b>Configuration</b>	Master Setup	X	X	-
	ECCOdownload Tool	-	-	X
<b>Supported OS</b>	Win 7 / Win 8 / Win 10 (32 and 64 bit) / Server 20003/2000	X	X	X
<b>Wireless interface</b>	Bluetooth Class 2, HID / SPP	X	-	-
	Bluetooth Class 1 HiD / SPP master/slave	-	X	-
	WiFi 802.11b/g	X	-	-
<b>Audio</b>	Speaker	X	X	X
	Buzzer	-	-	-
<b>Display</b>		-	-	-
<b>LED</b>	Red / Green / Yellow / Blue	X	X	X
<b>Keyboard</b>		4 keys	4 keys	4 keys
<b>Vibration</b>	Vibration Feedback	X	X	X
<b>Barcorde</b>	<b>1D Laser Module:</b> (EAN-8, EAN-13, UPC-A, UPC-E, Code 128, Code 39, Code 93, Interleaved 2of5, Chinese 2of5, Codabar, Codablock_F)	(X)	X	X
	<b>2D Imager:</b> (DataMatrix, QR Code, Micro QR, Aztec Code, Maxi Code, PDF417, MicroPDF)	(X)	-	-
<b>RFID</b>	<b>HF</b> 13.56 MHz ISO14443 / 15693 - (EU only)	(X)	-	-
	<b>UHF</b> 860 MHz, EPC GEN2, ISO18000-6C	(X)	-	-
	<b>UHF</b> 930 MHz, EPC GEN2, ISO18000-6C	(X)	-	-
<b>Size</b>		87 x 48 x 26 mm 3.42 x 1.89 x 1.02 in.	87 x 48 x 26 mm 3.42 x 1.89 x 1.02 in.	87 x 48 x 26 mm 3.42 x 1.89 x 1.02 in.
<b>Weight</b>		98 g / 3.46 oz.	96 g / 3.39 oz.	96 g / 3.39 oz.
<b>Battery</b>		1300 mAh, LiPo	1300 mAh, LiPo	1300 mAh, LiPo
<b>Sealing</b>		IP64	IP64	IP64
<b>Temperature Range</b>	Operation: 0°C up to 50°C (+32°F up to +122°F) Storage: -20°C up to 60°C (-4°F up to +140°F)	X	X	X